




# BEARING MANUFACTURING DE MEXICO, S.A.D...

10 mm x 26 mm x 8 mm NTN 6000LLU deep groove ball bearings



Bearing No. 6000LLU

6000LLU Bearing 2D drawings and 3D CAD models

Size	10x26x8 mm
Bore Diameter	10 mm
Outer Diameter	26 mm
Width	8 mm
d	10 mm
D	26 mm
B	8 mm
C	8 mm
r min.	0,3 mm
da min.	12 mm
da max	13,5 mm
Da max.	24 mm
ra max.	0,3 mm
Weight	0,019 Kg
Basic dynamic load rating (C)	4,55 kN
Basic static load rating (C0)	1,96 kN
Reference speed	21 000 r/min
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.019
EAN	4547359003543
Product Group	B00308
Enclosure	2 Seals



## BEARING MANUFACTURING DE MEXICO,S.A.D...

Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	10MM Bore; 26MM Outside Diameter; 8MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1   ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	<a href="http://www.ntnamerica.com">http://www.ntnamerica.com</a>
Manufacturer Item Number	6000LLU
Weight / LBS	0.042
Bore	0.394 Inch   10 Millimeter
Outside Diameter	1.024 Inch   26 Millimeter
Outer Race Width	0.315 Inch   8 Millimeter
bore diameter:	10 mm
precision rating:	ISO Class 0
outside diameter:	26 mm
finish/coating:	Uncoated
overall width:	8 mm
bearing material:	High Carbon Chrome Steel



## BEARING MANUFACTURING DE MEXICO,S.A.D...

bore type:	Round
cage material:	Steel
closure type:	Double Sealed
inner ring width:	8 mm
row type & fill slot:	Single Row Non-Fill Slot
outer ring width:	8 mm
snap ring included:	Without Snap Ring
maximum rpm (grease):	21000 rpm
internal clearance:	CN
fillet radius:	0.3 mm
operating temperature range:	-40 to 120 ° C
maximum rpm:	34000 RPM
dynamic load capacity:	4550 N
series:	60
static load capacity:	1960 N
manufacturer product page:	<a href="#">Click here</a>